



## ➔ ET1011 : Heavy Duty Tripod Turnstile

Passage Width :  $\leq 550$ mm  
 Throughput rate : 35p/m  
 Power Supply : 100 ~240V  
 Operational Voltage : 24V  
 Max Power Consumption : 30 W  
 Frequency : 50~60hz  
 Protection Level :  $\geq 44$   
 Working Temperature : -25 ~ +70°C  
 Electro - magnetic Drive : DC  
 Dimension Excluding Bar : 480x280x980 mm  
 Net Weight Including Bar : 44kg

### Features:

#### Controller

- ▶ Semi-Auto mode
- ▶ Full-Auto mode
- ▶ Pure Mechanical mode
- ▶ Single or Bi-directional function in mechanical and electrical versions

- ▶ Automatic reset of barrier arms after each passage

- ▶ Adjustable time out delay

#### Operating Mode

- ▶ Single passage in the set direction
- ▶ Bi-directional passage
- ▶ Free passage in the set direction
- ▶ Always free or locked

#### Secondary Controller :

- ▶ Users : 30,000 (RFID)
- ▶ Transaction storage : 1,00,000
- ▶ Integrated Controller : C3-200
- ▶ Relay : 12 V relay for lock
- ▶ Support Fire Alarm : Yes

#### Reader :

- ▶ RFID : Yes
- ▶ Protocol : RS485 / Mifare/Proxy (Optional) : Yes