



FB-TL-119

FB-TL-119

➔ Flap Barrier - FB-TL-119 (900mm)

Passage width (Max) : $\leq 900\text{mm}$
Throughput rate : 35 P/M
Power Supply : 100V ~ 240V AC
Operational Voltage : 24V DC
Max Power Consumption : 30W
Frequency : 50Hz ~ 60Hz
Protection Level (IP) : ≥ 44
Working Temperature : $-25^{\circ} \sim +70^{\circ}$
Electro-magnetic Drive : DC
Dimension excluding bars :
800 X 280 X 960 mm
Body Type : Stainless steel -304
Weight : FB-TL-119-L/R : 60kg

Feature :

- ▶ Use IC cards, ID cards, bar code or magnetic cards as automatic identification system.
- ▶ Display has been in use for statistics and numbers
- ▶ With voice and strobe light alerts
- ▶ A combination of infrared sensors and police anti-illegal entry into pedestrian access.
- ▶ Double anti-clipping function, photocell anti-clipping and mechanical anti-clipping
- ▶ The barrier can be set to delay closing in 1 ~ 60s after a valid card reading
- ▶ Single passage in the set direction
- ▶ Bi-directional single passage
- ▶ Plastic toughened glass
- ▶ Always free or locked