



Aiface Orcus

Display	2.4"@ TFT Color LCD Screen (320*240)
Camera	WDR Binocular Camera @ 1MP
Operation System	Linux
Hardware	CPU: Dual Core@1GHz RAM: 512MB; ROM: 8GB
Multiple Authentication method	Fingerprint / Face / Card / Password
Fingerprint Template Capacity	3,000
Face Template Capacity	1,500
Card Capacity	3,000
User Capacity	3,000
Transaction Capacity	1,50,000
Biometric Authentication Speed	Fingerprint: <0.5 sec; Facial Authentication: <0.35 sec
Facial Authentication Distance	30cm to 200cm
False Acceptance Rate (FAR) %	Visible Light Facial Authentication : FAR ≤ 0.01% Fingerprint : FAR ≤ 0.0001%
False Rejection Rate (FRR) %	Visible Light Facial Authentication : FRR ≤ 0.02% Fingerprint : FRR ≤ 0.01%

Available RFID Module	Proximity Card@125 kHz (Standard) Mifare Card@13.56 MHz (Optional)
Communication	TCP/IP, Wi-Fi (Optional), USB
Access Control Interface	Electro Magnetic Lock/ Electric Lock, Door Sensor, Exit Button
Power Supply	DC 12V 1.5A
Operating Temperature	-5°C to 45°C
Operating Humidity	20% to 80% RH (Non-condensing)
Dimensions	205.20 mm*74.19 mm*33.30 mm (L*W*H)
Supported Software	eTimetracklite Software, eBioServer

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.