



## FACE - AIFACE-MARS+HID

### TECHNICAL SPECIFICATIONS

- Display : 5inch Touch Screen
- Face Capacity : 3000
- HID Card Capacity : 3000
- Transactions : 150000
- Operation System : Linux
- Hardware : 900MHZ Dual Core CPU Memory 512MB RAM / 8G ROM 2MP WDR Low Light Camera Adjustable Light Brightness LED
- Communication : TCP/IP, WiFi(Optional), Wiegand Input/Output, RS485
- Access Control Interface : Electro Magnetic Lock/ Electric Lock, Door Sensor, Exit Button, Alarm Output
- Face Recognition Speed :  $\leq 1$ s
- Power Supply : 12V 3A
- Working Humidity : 10%-90%
- Working Temperature -10 °C- 45 °C
- Dimensions (W\*H\*D) : 91.93\*202.93\*21.5mm
- Supported Software : eTimeTracklite

### FEATURES

- Visible Light Facial Recognition
- Anti-spoofing algorithm against print attack(laser, color and B/W photos), videos attack and 3D mask attack
- Multiple Verification: Face / HID Card / Password

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.  
[www.esslsecurity.com](http://www.esslsecurity.com)